

# K-KONDENSA DRUKODRAIN PLUS

Drain for compressed air condensate


**HANSA FLEX**

## Vlastnosti

Pripojovacie vedenie filter 100 m<sup>3</sup>/min

Pripojovacie vedenie kompresor 10 m<sup>3</sup>/min

Pripojovacie vedenie sušič 20 m<sup>3</sup>/min



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Compact and exceptionally reliable, level-controlled drain for compressed air condensate. The condensate enters the integrated collecting tank, in which the level is continuously monitored. When the condensate reaches the maximum mark, the pilot valve opens and the condensate is forced into the discharge line by the system pressure. The valve closes again when the level reaches the minimum mark. Benefits of »drukodrain plus«: No pressure loss, Diaphragm protected by integrated cup filter, Test button for manual outlet, Auto-reset function, Suitable for all condensate types.

## Pokyny pre objednanie

The following voltages on request: 24 VDC, 24 VAC DC, 24 VAC / 50 Hz, 110 VAC / 50 Hz, 115 V / 50 Hz

## Výrobok

Označenie	Prevádzkový tlak	Napätie
K- 07 25 09 24	0.2 - 16 bar	230 VAC / 50 Hz