


| Vlastnosti   |                           |
|--------------|---------------------------|
| Vstupný tlak | Max. 15 bar               |
| Prípojka     | G 1/4 internal / external |
| Materiál     | Mosadz                    |





## Poznámka

Dependent on the input pressure P1, the initial pressure P2 can vary between -20% to +20% Ďalšie údaje na vyžiadanie.

## **Popis**

| Výrobok        |                 |                         |            |        |             |            |
|----------------|-----------------|-------------------------|------------|--------|-------------|------------|
| Označenie      | Tlak nastavenia | max. prietok<br>(L/min) | A:<br>(mm) | В      | Ø C<br>(mm) | SW<br>(mm) |
| K- 07 25 19 31 | 2,0             | 300                     | 34,0       | 9,0 mm | 17,0        | 17         |
| K- 07 25 02 00 | 3,0             | 360                     | 34,0       | 9,0 mm | 17,0        | 17         |
| K- 07 25 02 01 | 4,0             | 380                     | 34,0       | 9,0 mm | 17,0        | 17         |
| K- 07 25 02 02 | 5,0             | 390                     | 34,0       | 9,0 mm | 17,0        | 17         |
| K- 07 25 02 03 | 6,0             | 405                     | 34,0       | 9,0 mm | 17,0        | 17         |
| K- 07 25 19 32 | 7,0             | 415                     | 34,0       | 9,0 mm | 17,0        | 17         |
| K- 07 25 19 33 | 8,0             | 420                     | 34,0       | 9,0 mm | 17,0        | 17         |