

# K-FLASCHENDRUCKR 200 N GASE

Regulátor tlaku s odkaľovacou nádobou, tlak v nádobe 200 bar, pre nehorľavé plyny


**HANSA FLEX**

## Vlastnosti

**Manometer objemu** 0 - 200/315 bar (max. cylinder pressure 200 bar),  
0 - 300/400 bar (max. cylinder pressure 300 bar),  
0 - 18/40 bar for acetylene

**Materiál** Lisovaná mosadz

**Pripojenie nádoby** Nut 3/4



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Single-stage type of construction acc. to DIN EN ISO 2503, with shut-off valve and safety valve as well as pressure gauges for the cylinder contents and working pressure.

## Výrobok

Označenie	Druh plynu	Prevádzkový tlak
K- 07 25 07 11	Oxygen	0 - 10,0 bar
K- 07 25 07 12	Oxygen	0 - 20,0 bar
K- 07 25 07 14	Compressed air	0 - 10,0 bar
K- 07 25 07 15	Compressed air	0 - 20,0 bar
K- 07 25 07 16	Nitrogen	0 - 10,0 bar
K- 07 25 07 17	Nitrogen	0 - 20,0 bar
K- 07 25 07 18	Carbon dioxide	0 - 10,0 bar
K- 07 25 07 19	Carbon dioxide	0 - 20,0 bar
K- 07 25 07 20	Argon/helium	0 - 10,0 bar

## Náhradné diely

K-MANO SCHWEISSTECHNIK	Content pressure gauge
K-MANO SCHW	Pressure gauges for welding
K-SCHUTZKAPPE MANOMETER	Ochranný kryt