

K-ANFAV MULTIFIX

Start-up valves

HANSA FLEX

Vlastnosti

| | |
|-------------------------------|--|
| Vstupný tlak | Min. 2 bar, max. 16 bar |
| Teplota média | max. 60 °C |
| Teplota okolia | Max. 60 °C |
| Tesniaci materiál | NBR |
| Kryt | Die-cast zinc, Aluminium for G 3/4 and G 1 variant |
| Meranie prietochného množstva | At P1 = 6 bar and pressure drop $\Delta p = 1$ bar |



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Seat valves operated by secondary pressure for controlled pressurisation of pneumatic systems. The full cross-section of the regulator is opened at 50% of the input pressure. The filling time can be altered by turning the adjusting screw.

Výrobok

| Označenie | Závit | Prietok (L/min) | A: (mm) | B | D: (mm) |
|----------------|-------|-----------------|---------|----------|---------|
| K- 07 25 11 54 | G 1/4 | 1000 | 47,8 | 54,2 mm | 26,8 |
| K- 07 25 11 55 | G 1/2 | 4000 | 68,8 | 71,6 mm | 35,1 |
| K- 07 25 19 34 | G 3/4 | 12000 | 99,7 | 104,0 mm | 52,0 |
| K- 07 25 19 35 | G 1 | 12000 | 99,7 | 104,0 mm | 52,0 |

Náhradné diely

| | |
|---------------------|-----------------|
| K-KOPPELPAKET MEHR | Coupling packet |
| K-KOPPELPAKET SCHMA | Coupling packet |