


K-FI REGL METALLBEHAE S MANO MULTIF

Filter regulators with metal bowl and sight glass, incl. pressure gauge

HANSA FLEX

Vlastnosti

Vstupný tlak	Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Teplota média	max. 60 °C
Teplota okolia	Max. 60 °C
Veľkosť pórov vo filtračnej vložke	5 µm (C55: 40 µm)
Tesniaci materiál	NBR
kryt pružiny	POM-brass
Kryt	Die-cast zinc, Aluminium for G 1 variant
Drain valve	Semi-automatic
Meranie prietoku množstva	At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Reversible diaphragm pressure regulators, independent of inlet pressure, with secondary ventilation, in combination with a centrifugal separator. The pressure setting can be locked by pressing in the handwheel.

Pokyny pre objednanie

Filter regulators with bowl guard and metal bowl are also available with control ranges of 0.1 - 3 bar, 0.2 - 6 bar and 0.5 - 16 bar. Please ask for more information. Lockable filter regulators available on request.

Výrobok

Označenie	Závit	Rozsah regulácie	Prietok (L/min)	A: (mm)	B	C (mm)	D: (mm)	DN	Veľkosť
K- 07 25 00 68	G 1/4	0.5 - 10 bar	1500	47,8	192,0 mm	67,0	125,5	6	1
K- 07 25 00 72	G 3/8	0.5 - 10 bar	1500	47,8	192,0 mm	67,0	125,5	10	1
K- 07 25 00 76	G 1/2	0.5 - 10 bar	3500	68,8	246,0 mm	99,0	149,2	15	2
K- 07 25 00 80	G 3/4	0.5 - 10 bar	3500	68,8	246,0 mm	99,0	149,2	20	2
K- 07 25 00 84	G 1	0.5 - 10 bar	12000	100,0	385,0 mm	128,0	255,7	25	3

Náhradné diely

K-HALTERBAUSATZ	Holder
K-SCHALTTAFELMUTTER	Nut
K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-METALLBEHAELTER OELER MULTIFIX	Metal tank oiler
K-PC-BEHAELTER FILTER MULTIFIX	Polycarbonate tank filter
K-SCHUTZKORB G	Protective cage
K-VERSCHLEI-SATZ	Set of wearing parts
K-FILTERELEMENT	Filter element
K-AUTOMAT ABLASSVENTIL	Automatic drain valve