

# K-VT SCHMAL MULTIFIX

Manifolds - narrow design

**HANSA FLEX**

## Vlastnosti

Vstupný tlak	Max. 16 bar
Teplota média	max. 60 °C
Teplota okolia	Max. 60 °C
Tesniaci materiál	NBR
Kryt	Die-cast zinc
Meranie prietoku množstva	At P1 = 6 bar and pressure drop $\Delta p = 1$ bar



## Poznámka

Flow rate l/min at P → A  
Ďalšie údaje na vyžiadanie.

## Popis

Wide or narrow, four-way manifolds.

## Výrobok

Označenie	Outlets	Závit	Prietok (L/min)	A: (mm)	B	C (mm)
K- 07 25 11 82	3 x 1/4, 1 x 1/8	G 1/4	3300	34,8	52,0 mm	26,0
K- 07 25 11 83	1 x 3/8, 2 x 1/4, 1 x 1/8	G 1/2	11000	38,8	67,0 mm	33,5

## Príslušenstvo

K-DRS WECHSELKONTAK ANFLANSCHBAR DS	Pressure switches, changeover type, suitable for flange mounting K-07302861
K-ZUBEH HANSA	Accessories for pressure switch HANSA

## Náhradné diely

K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet