

K-SCHALTVENTILE 3/2 MULTIFIX MINI

On-off valves (3/2-way valves)

HANSA FLEX

Vlastnosti

| | |
|----------------------------|--|
| Vstupný tlak | Min. 2 bar, max. 10 bar |
| Teplota média | max. 60 °C |
| Teplota okolia | Max. 60 °C |
| Elektrické pripojenie | Device plug PG 9, type B, EN 175301-803 |
| Krytie | IP 65 (P 54) acc. to DIN 40050 |
| Prietok | 1600 l/min |
| Trvanie zapnutia relatívne | 100 % |
| Pripojenie odvodu vzduchu | Silencer G 1/4 |
| Tesniaci materiál | NBR |
| Kryt | Die-cast zinc |
| Meranie prietoku množstva | At P1 = 6 bar and pressure drop $\Delta p = 1$ bar |



Poznámka

If several devices in the »multiflex-mini« Series are assembled together, the maximum working pressure is 12 bar.

Ďalšie údaje na vyžiadanie.

Popis

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal. When they are switched off, the system is relieved at the same time.

Výrobok

| Označenie | Závit | Magnetická cievka | A: (mm) | B | C (mm) | Veľkosť |
|----------------|-------|-------------------|------------|---------|-----------|---------|
| K- 07 25 11 62 | G 1/4 | 230 V AC, 50 Hz | 45,0 | 29,0 mm | 96,0 | 0 |
| K- 07 25 11 63 | G 1/4 | 110 V AC, 50 Hz | 45,0 | 29,0 mm | 96,0 | 0 |
| K- 07 25 11 64 | G 1/4 | 24 V DC | 45,0 | 29,0 mm | 96,0 | 0 |

Náhradné diely

| | |
|------------------------------|-------------------------------------|
| K-KOPPELPAKET MEHR | Coupling packet |
| K-GERAETESTECKER | Coupling socket |
| K-AUTOMAT ABLASSVENTIL | Automatic drain valve |
| K-MAGNETSPULE MULTIFIX | Solenoid |
| K-SCHALLDAE SINTERBR SCHLITZ | Silencers, sintered bronze, slotted |