

# K-DV STECK B RAENDEL

Bidirectional flow control valves, air restriction at both ends (»B«), plug-in connector

**HANSA FLEX**

## Vlastnosti

|  |                                    |
|--|------------------------------------|
| Prevádzkový tlak                               | max. 10 bar                        |
| Rozsah teplôt                                  | 0 °C to +70 °C                     |
| dutá skrutka, otočné rameno, regulačná skrutka | Nickel-plated brass                |
| vnútorné diely                                 | Brass with a bare metal surface    |
| Tesnenie hubice O-krúžok                       | NBR                                |
| tesnenia (nestratiteľné)                       | Polyamide (glass fibre-reinforced) |



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

For regulation of a cylinder piston speed at both ends and control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly. <br>On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

## Výrobok

| Označenie      | C<br>(mm) | pre hadicu | Závit | SW    | B<br>(mm) |
|----------------|-----------|------------|-------|-------|-----------|
| K- 07 15 04 83 | 18,6      | 4 mm       | M 5   | 8 mm  | 38,9      |
| K- 07 15 04 87 | 20,6      | 4 mm       | G 1/8 | 14 mm | 42,0      |
| K- 07 15 04 88 | 22,7      | 6 mm       | G 1/8 | 14 mm | 42,0      |
| K- 07 15 04 89 | 23,7      | 8 mm       | G 1/8 | 14 mm | 42,0      |
| K- 07 15 04 85 | 24,2      | 6 mm       | G 1/4 | 17 mm | 51,0      |
| K- 07 15 04 86 | 24,7      | 8 mm       | G 1/4 | 17 mm | 51,0      |
| K- 07 15 04 84 | 26,8      | 10 mm      | G 1/4 | 17 mm | 51,0      |