


K-KURZH ZYL EINFACHW

Short-stroke cylinders, single-acting (magnetic)

HANSA FLEX

Vlastnosti

Médiá	Filtered compressed air, lubricated (ensure continuity) or unlubricated
Prevádzkový tlak	max. 10 bar
Reakčný tlak	0,6 bar (Ø 12 bis Ø 32), 0,4 bar (Ø 40 bis Ø 80)
Rozsah teplôt	-10 °C to +80 °C
Piestová tyč	C45 steel, hard chrome-plated
rúrka	Aluminium alloy, anodised
Priemer hlavy	Ø 12 to Ø 25 painted brass, Ø 32 to Ø 80 aluminium
Piest	Ø 12 to Ø 63 synthetic (acetal) resin, Ø 80 alu/PTFE
tesnenie piestovej tyče	NBR (additional charge for PU and FKM)
piestové tesnenie	NBR (additional charge for PU and FKM)



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Suitable for installation in limited spaces, with magnet.

Dodatočné informácie

Important: The scope of supply does not include a connector. Please order separately.

Other types, e.g. increased thermal stability, non-standard strokes, through rod, non-rotating version, etc., available on request.

Výrobok

Označenie	Ø piest	Zdvih (mm)	Prípojka	Vnútrotný závit piestovej tyče
K- 07 15 11 87	12 mm	10	M 5	M 3
K- 07 15 11 88	12 mm	25	M 5	M 3
K- 07 15 11 89	16 mm	10	M 5	M 5
K- 07 15 11 90	16 mm	25	M 5	M 5
K- 07 15 11 91	20 mm	10	M 5	M 5
K- 07 15 11 92	20 mm	25	M 5	M 5
K- 07 15 11 93	25 mm	10	G 1/8	M 5
K- 07 15 11 94	25 mm	25	G 1/8	M 5
K- 07 15 11 95	32 mm	10	G 1/8	M 6
K- 07 15 11 96	32 mm	25	G 1/8	M 6
K- 07 15 11 97	40 mm	10	G 1/8	M 6
K- 07 15 11 98	40 mm	25	G 1/8	M 6
K- 07 15 11 99	50 mm	25	G 1/8	M 8
K- 07 15 12 00	63 mm	25	G 1/8	M 8

Príslušenstvo

K-MAGNETSENSOREN-REED Reed magnetic sensor (incl. 2.5 m cable)