


K-STOPPVENTILE STECK

Stop valves, ports 2 and 3 with plug connection

HANSA FLEX

Vlastnosti

| | |
|-------------------|---|
| Pracovný tlak | Max. 10 bar |
| Riadiaci tlak | 1 - 5 bar, depending on operating pressure |
| Teplota média | max. 70 °C |
| Montážna poloha | Any. Ring pieces can still be rotated 360° after the valve has been tightened |
| Tesniaci materiál | Perbunan |



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

For high-speed positioning and stop functions as well as emergency switching (e.g. emergency stop). If a control signal is present at port 3, air can flow to and from the cylinder. If no control signal is present, the air flow to and from the cylinder is shut off, causing the cylinder to stop in the required position. Stop valves are screwed directly onto the cylinder instead of the normal pipe connections.

Výrobok

| Označenie | Port 1 | Port 2 | Prípojka 3 | Materiál | B (mm) | C (mm) |
|----------------|--------|--------|------------|---------------------|-----------|-----------|
| K- 07 15 20 50 | G 1/8 | 6 mm | 4 mm | Nickel-plated brass | 52,0 | 25,0 |
| K- 07 15 20 49 | G 1/4 | 6 mm | 4 mm | Nickel-plated brass | 58,0 | 28,0 |
| K- 07 15 20 51 | G 3/8 | 8 mm | 4 mm | Nickel-plated brass | 63,0 | 32,0 |
| K- 07 15 20 48 | G 1/2 | 12 mm | 4 mm | Nickel-plated brass | 72,0 | 41,0 |