

K-WV 3/2 ELEKTROPNEUMATISCH

3/2-way pilot valves

HANSA FLEX

Vlastnosti

| | |
|----------------------|--|
| Prevádzkový tlak | 2,5 - 10 bar (monostable)\n1,0 - 10 bar (bistable)\n\nvacuum up to 10 bar (external pilot air) |
| min. pracovný tlak | 2.5 bar (monostable), 1.0 bar (bistable) |
| Rozsah teplôt | -10 °C to +60 °C |
| Prietok 6bar a 10bar | 550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2) |
| Prietok 6bar a 5bar | 400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2) |



Poznámka

Ďalšie údaje na vyžiadanie.

Výrobok

| Označenie | Prípojka | Napätie | DN | funkcia | Schéma zapojenia číslo | Riadenie |
|----------------|----------|--------------|----|------------|------------------------|----------|
| K- 07 15 00 23 | G 1/8 | 24 V DC | 5 | 3/-way NO | 32 | |
| K- 07 15 00 24 | G 1/4 | 24 V DC | 8 | 3/-way NO | 32 | |
| K- 07 15 25 75 | G 3/8 | 24 V DC | 13 | 3/-way NO | 32 | |
| K- 07 15 00 25 | G 1/2" | 24 V DC | 15 | 3/-way NO | 32 | |
| K- 07 15 00 26 | G 1/8 | 230 V, 50 Hz | 5 | 3/-way NO | 32 | |
| K- 07 15 00 27 | G 1/4 | 230 V, 50 Hz | 8 | 3/-way NO | 32 | |
| K- 07 15 25 76 | G 3/8 | 230 V, 50 Hz | 13 | 3/-way NO | 32 | |
| K- 07 15 00 28 | G 1/2" | 230 V, 50 Hz | 15 | 3/-way NO | 32 | |
| K- 07 15 00 29 | G 1/8 | 24 V DC | 5 | 3/2-way NC | 33 | |
| K- 07 15 00 30 | G 1/4 | 24 V DC | 8 | 3/2-way NC | 33 | |
| K- 07 15 25 77 | G 3/8 | 24 V DC | 13 | 3/2-way NC | 33 | |
| K- 07 15 00 31 | G 1/2" | 24 V DC | 15 | 3/2-way NC | 33 | |
| K- 07 15 00 32 | G 1/8 | 230 V, 50 Hz | 5 | 3/2-way NC | 33 | |
| K- 07 15 00 33 | G 1/4 | 230 V, 50 Hz | 8 | 3/2-way NC | 33 | |
| K- 07 15 25 78 | G 3/8 | 230 V, 50 Hz | 13 | 3/2-way NC | 33 | |
| K- 07 15 00 34 | G 1/2" | 230 V, 50 Hz | 15 | 3/2-way NC | 33 | |
| K- 07 15 00 35 | G 1/8 | 24 V DC | 5 | 3/2-way | 34 | |
| K- 07 15 00 36 | G 1/4 | 24 V DC | 8 | 3/2-way | 34 | |
| K- 07 15 25 79 | G 3/8 | 24 V DC | 13 | 3/2-way | 34 | |
| K- 07 15 00 37 | G 1/2" | 24 V DC | 15 | 3/2-way | 34 | |
| K- 07 15 00 38 | G 1/8 | 230 V, 50 Hz | 5 | 3/2-way | 34 | |
| K- 07 15 00 39 | G 1/4 | 230 V, 50 Hz | 8 | 3/2-way | 34 | |
| K- 07 15 25 80 | G 3/8 | 230 V, 50 Hz | 13 | 3/2-way | 34 | |
| K- 07 15 00 40 | G 1/2" | 230 V, 50 Hz | 15 | 3/2-way | 34 | |