

# K-WV 5/3 ELEKTROPNEU MITTELSTELLUNG

5/3-way pilot valves (monostable)

**HANSA FLEX**

## Vlastnosti

Prevádzkový tlak	2,5 - 10 bar (monostable) \n 1,0 - 10 bar (bistable) \n vacuum up to 10 bar (external pilot air)
min. pracovný tlak	2.5 bar (monostable), 1.0 bar (bistable)
Rozsah teplôt	-10 °C to +60 °C
Prietok 6bar a 10bar	550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2)
Prietok 6bar a 5bar	400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2)



## Poznámka

Ďalšie údaje na vyžiadanie.

## Výrobok

Označenie	Prípojka	Napätie	DN	funkcia	Schéma zapojenia číslo
K- 07 15 03 30	G 1/8	24 V DC	5	5/3-way	37
K- 07 15 03 31	G 1/4	24 V DC	8	5/3-way	37
K- 07 15 25 87	G 3/8	24 V DC	13	5/3-way	37
K- 07 15 03 32	G 1/2"	24 V DC	15	5/3-way	37
K- 07 15 03 33	G 1/8	230 V, 50 Hz	5	5/3-way	37
K- 07 15 03 34	G 1/4	230 V, 50 Hz	8	5/3-way	37
K- 07 15 25 88	G 3/8	230 V, 50 Hz	13	5/3-way	37
K- 07 15 03 35	G 1/2"	230 V, 50 Hz	15	5/3-way	37
K- 07 15 03 36	G 1/8	24 V DC	5	5/3-way	38
K- 07 15 03 37	G 1/4	24 V DC	8	5/3-way	38
K- 07 15 25 89	G 3/8	24 V DC	13	5/3-way	38
K- 07 15 03 38	G 1/2"	24 V DC	15	5/3-way	38
K- 07 15 03 39	G 1/8	230 V, 50 Hz	5	5/3-way	38
K- 07 15 03 40	G 1/4	230 V, 50 Hz	8	5/3-way	38
K- 07 15 25 90	G 3/8	230 V, 50 Hz	13	5/3-way	38
K- 07 15 03 41	G 1/2"	230 V, 50 Hz	15	5/3-way	38
K- 07 15 03 42	G 1/8	24 V DC	5	5/3-way	39
K- 07 15 25 91	G 3/8	24 V DC	13	5/3-way	39
K- 07 15 03 43	G 1/4	24 V DC	8	5/3-way	39
K- 07 15 03 44	G 1/2"	24 V DC	15	5/3-way	39
K- 07 15 03 45	G 1/8	230 V, 50 Hz	5	5/3-way	39
K- 07 15 03 46	G 1/4	230 V, 50 Hz	8	5/3-way	39
K- 07 15 25 92	G 3/8	230 V, 50 Hz	13	5/3-way	39
K- 07 15 03 47	G 1/2"	230 V, 50 Hz	15	5/3-way	39