

# K-WV 3/2 MANU K DREHHEBEL

3/2-way pilot valves, manually operated, with short wing lever, NC

**HANSA FLEX**

## Vlastnosti

|                      |   |
|----------------------|---|
| Prevádzkový tlak     | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| Rozsah teplôt        | -10 °C to +60 °C  |
| Prietok 6bar a 10bar | 550 NI/min  |
| Prietok 6bar a 5bar  | 400 NI/min  |
| teleso ventila       | Hliník  |
| pružina              | Special steel   |
| Piest                | Aluminium   |
| Tesniaci materiál    | NBR   |



## Poznámka

3 valve positions only in conjunction with a second 3/2-way valve. <br>Corresponds to a 5/3-way valve.

Ďalšie údaje na vyžiadanie.

## Dodatočné informácie

Important: The scope of supply does not include a connector. Please order separately.

## Výrobok

| Označenie      | Prípojka | Symbol | Stlačenie  | Spínacie polohy |
|----------------|----------|--------|------------|-----------------|
| K- 07 15 00 78 | G 1/8    | 5      | monostable | 2               |
| K- 07 15 00 79 | G 1/8    | 6      | bistabilný | 2               |
| K- 07 15 00 80 | G 1/8    | 7      | monostable | 3*              |
| K- 07 15 00 81 | G 1/8    | 8      | bistabilný | 3*              |