

K-WV 5/2 MANU K DREHHEBEL

5/2-way pilot valves, manually operated, with short wing lever

HANSA FLEX

Vlastnosti

| | |
|----------------------|---|
| Prevádzkový tlak | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| Rozsah teplôt | -10 °C to +60 °C |
| Prietok 6bar a 10bar | 550 NI/min |
| Prietok 6bar a 5bar | 400 NI/min |
| teleso ventilu | Hliník |
| pružina | Special steel |
| Piest | Aluminium |
| Tesniaci materiál | NBR |



Poznámka

*3 valve positions only in conjunction with a second way valve.

Ďalšie údaje na vyžiadanie.

Dodatočné informácie

Important: The scope of supply does not include a connector. Please order separately.

Výrobok

| Označenie | Prípojka | Symbol | Stlačenie | Spínacie polohy |
|----------------|----------|--------|------------|-----------------|
| K- 07 15 02 37 | G 1/8 | 5 | monostable | 2 |
| K- 07 15 02 38 | G 1/8 | 6 | bistabilný | 2 |
| K- 07 15 02 39 | G 1/8 | 7 | monostable | 3* |
| K- 07 15 02 40 | G 1/8 | 8 | bistabilný | 3* |