

# K-BKR MINI BLAUER GR

Mini ball valves with blue wing lever surface

**HANSA FLEX**

## Vlastnosti

Prevádzkový tlak	max. 10 bar
Popis závitů	Female thread G (DIN EN ISO 228-1), Male thread R (ISO 7-1)
Teplota média	-10 °C to +80 °C
otočná páčka	Plastic
Kryt a guľa	Nickel-plated brass
Tesnenie gule	PTFE
Tesnenie vretena	NBR



## Poznámka

Ďalšie údaje na vyžiadanie.

## Výrobok

Označenie	DN	Závit	V (mm)	D (mm)	L1 (mm)	SW (mm)
K- 07 30 20 06	6	G 1/8 female	23,0	34,0	24,0	15
K- 07 30 20 07	6	G 1/4 female	23,0	38,0	24,0	15
K- 07 30 20 08	8	G 3/8 female	24,0	43,0	24,0	17
K- 07 30 20 09	10	G 1/2 female	27,0	49,0	24,0	21
K- 07 30 20 02	6	G 1/8 female / R 1/8 male	23,0	34,0	24,0	15
K- 07 30 20 03	6	G 1/4 female / R 1/4 male	23,0	39,0	24,0	15
K- 07 30 20 04	8	G 3/8 female / R 3/8 male	24,0	43,0	24,0	17
K- 07 30 20 05	10	G 1/2 female / R 1/2 male	27,0	50,0	24,0	21