


K-HS PTFE DICHTRING EINFACH

Banjo bolts with PTFE seal, single

HANSA FLEX

Vlastnosti

| | |
|------------------------|---|
| Pracovný tlak impulzný | Max. 10 bar |
| Tlak | Max. 15 bar (depending on pipe quality) |
| vhodný materiál rúrky | PVDF, PTFE, stainless steel, PA, PU |
| Norma | G thread acc. to DIN EN ISO 228-1 |
| Teplota okolia | -20 °C to max. +150 °C (depending on pipe quality and diameter) |
| Materiál | Ušľachtilá oceľ 1.4404 |
| Tesniaci materiál | FKM |



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Výrobok

| Označenie | Závit | L1 (mm) | SW |
|----------------|-------|------------|-------|
| K- 07 40 47 04 | G 1/8 | 29,0 | 14 mm |
| K- 07 40 47 03 | G 1/4 | 32,5 | 17 mm |
| K- 07 40 47 05 | G 3/8 | 36,0 | 21 mm |
| K- 07 40 47 02 | G 1/2 | 41,5 | 26 mm |