


K-LKM S NW7,4 SCHL TUE

Safety couplings DN 7.4, with hose stem

HANSA FLEX

Vlastnosti

Prevádzkový tlak	Max. 12 bar, maximum static working pressure (non-pulsating)
Prevádzkový tlak zásuvné priechodky a vsuvky	0 to 35 bar
Prietok vzduch	1.300 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Teplota média	-20 °C to +60 °C
kryt, teleso ventilu	Nickel-plated brass
Ventil	Brass
uvoľňovacie puzdro	Plastic
pružina, rozperný krúžok, kofky, gule	Stainless steel
Tesniaci materiál	NBR



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

One-hand air relief couplings with double locking system. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the sleeve again. The coupling can now be disconnected. This system meets the requirements of ISO 4414 and is BIA-compliant (BIA = industrial safety institute).

Výrobok

Označenie	Prípojka	Dĺžka (mm)	SW (mm)
K- 07 35 03 04	Stem, I.D. 6	71,2	22
K- 07 35 03 05	Stem, I.D. 8	71,2	22
K- 07 35 03 06	Stem, I.D. 9	71,2	22
K- 07 35 03 07	Stem, I.D. 10	71,2	22
K- 07 35 03 08	Stem, I.D. 13	71,2	22

Prídavné elementy

K-NIPPEL KUPPL NW7 AG VZ	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male
K-NIPPEL KUPPL NW7 IG VZ 2	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, female
K-TUE 7,2 7,8 ST VZ 1	Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,