

K-MV O (NO) V 24 V DC 1

Normally open, (NO), pilot-operated, 24 V DC


HANSA FLEX

Vlastnosti

Elektrické pripojenie	device socket type A in acc. with ISO 4400 for all valves with threads G 3/8 & G 1/2, except valves type 3 & 4. Device socket
Krytie	IP 65
Teplota média	max. 80 °C when using water or oils; max. 90 °C when using with air
Popis závit	G thread acc. DIN EN ISO 228-1
kryt, sedlo ventila	Brass
vnútorné diely	Stainless steel
tesnenie	FPM



④



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Standard series in two different versions: Directly operated, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Výrobok

Označenie	Závit	max. prevádzkový tlak (bar)	min. prevádzkový tlak (bar)	MS	A: (mm)	B (mm)	C (mm)	vyhotovenie
K- 07 30 01 97	G 1/2	7	0,50	15,0	70,0	70,0	112,3	4
K- 07 30 01 98	G 3/4	7	0,50	20,0	70,0	82,0	120,8	4
K- 07 30 01 99	G 1	7	0,50	25,0	70,0	82,0	129,3	4