

K-SCHLAUCHTUELLEN KUPP

Hose stems for couplings DN 7.2 - DN 7.8, swivel type, nickel-plated brass / steel, male

HANSA FLEX

Vlastnosti

Prevádzkový tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
Prietok vzduch	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Teplota média	0 °C to +70 °C
kryt, puzdro, teleso ventilu	Nickel-plated brass
pružina, rozperný krúžok, gule	Stainless steel
Tesniaci materiál	NBR



Poznámka

Ďalšie údaje na vyžiadanie.

Výrobok

Označenie	Prípojka	LW (mm)	Materiál
K- 07 35 02 02	G 1/4 male	6	Nickel-plated brass
K- 07 35 02 03	G 1/4 male	8	Nickel-plated brass
K- 07 35 02 04	G 1/4 male	9	Nickel-plated brass
K- 07 35 02 05	G 1/4 male	10	Nickel-plated brass
K- 07 35 01 78	G 1/4 male	13	Nickel-plated brass
K- 07 35 02 15	R 3/8 male	6	Nickel-plated steel
K- 07 35 02 16	R 3/8 male	9	Nickel-plated steel