# K-SCHLAUCH KUPPLUNG SET SICH

Hose and coupling kits, with straight hose and DN 7.6 safety coupling

## Vlastnosti

| | |
|---|---|
| **Prevádzkový tlak** | 16 bar |
| **Teplota média** | -20 °C to +60 °C |



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Couplings: High-grade single-handed quick-release coupling and safety coupling in steel / brass zinc-plated for high flow rates, specially designed for all applications with high mechanical wear. Strong, impact- and vibration-resistant construction for challenging applications. Polyurethane hose Exceedingly flexible, extremely kink-resistant and tolerant of dirt spiral hose with high resilience under tear, tensile and impact loads with a long service life and outstanding ageing qualities. It is also UV resistant and has outstanding abrasion resistance.

## Výrobok

| Označenie | Rozmer hadice | Pracovná dĺžka (m) |
|---|---|---|
| **K- 07 10 05 58** | 12 mm x 8 mm | 10,0 |
| **K- 07 10 05 59** | 12 mm x 8 mm | 15,0 |
| **K- 07 10 05 60** | 16 mm x 11 mm | 10,0 |
| **K- 07 10 05 61** | 16 mm x 11 mm | 15,0 |