

K-DROSSELPLATT NAMUR VENTIL

Flow regulators for NAMUR valves

HANSA FLEX

Vlastnosti

Médiá	Air, neutral gases, filtered
Pracovný tlak	0.5 to 10 bar
Prevádzková teplota	-20 °C to +70 °C
Je zahrnuté v rozsahu dodávky	1 coding pin (not for K-07152240), 2 O-rings, 2 fixing screws
Kryt	Aluminium, anodised
Materiál	Tesnenie: NBR
Tesniaci materiál	NBR



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Block-form flow regulator as an intermediate plate between the control valve and actuator acc. to the G 1/4 NAMUR standard. 3/2-way flow regulators: Independent regulation of the forward and return strokes of a single-acting pneumatic actuator. 5/2-way flow regulators: Regulation of the forward and return strokes of a double-acting pneumatic actuator.

Výrobok

Označenie	funkcia	Stlačenie	DN	Prietok (L/min)
K- 07 15 22 39	3/2-way	Knurled Screw	5	650
K- 07 15 22 40	3/2-way	Screwdriver	5	650
K- 07 15 22 41	5/2-way	Knurled Screw	5	650
K- 07 15 22 42	5/2-way	Screwdriver	5	650