

# K-ZWEIHAND S VENTILE O GEH

Two-hand safety valve without housing

**HANSA FLEX**

## Vlastnosti

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| Médiá                               | Filtered, unlubricated compressed air |
| Prevádzkový tlak                    | 2.5 - 8 bar                           |
| Rozsah teplôt                       | -10 °C to +60 °C                      |
| Prípojka                            | Push-in fitting for pipe 4 mm         |
| Stlačenie                           | Pneumatic                             |
| Prietokné množstvo vzduchu 6bar     | 85 NI/min                             |
| max. časový posuv vstupného signálu | 0,4 s                                 |



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

This pushbutton panel according to EN574 Type III A is comprised of a dual manual control valve with a housing and manifold. The valve only generates an output signal if two synchronised input signals are received within < 0.4 sec. If one input signal is interrupted, the output signal is interrupted as well. An emergency stop valve with a mushroom pushbutton is included. The housing can be screwed to the wall in any position. The valve manifold can optionally be supplied without the housing and with a DIN bar adapter. Applications: Two-hand safety valve for start-of-cycle control on a pneumatically operated machine.

## Výrobok

| Označenie      | Definícia                             | Prípojka                      |
|----------------|---------------------------------------|-------------------------------|
| K- 07 15 26 09 | Two-hand safety valve without housing | Push-in fitting for 4 mm pipe |
| K- 07 15 26 10 | mounting element                      | -                             |