

K-BKR BLAU STAHLHEBEL IG AG

Ball valves with blue steel lever, lightweight type, female/male thread

HANSA FLEX

Vlastnosti

| | |
|----------------------------|--|
| Oblasť použitia | Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture |
| Prevádzkový tlak | Max. 40 bar |
| Prevádzková teplota | -15 °C to +90 °C |
| Popis závit | G thread acc. DIN EN ISO 228-1 |
| Kryt | Nickel-plated brass |
| páka | Steel, with plastic coating |
| guľa | Chrome-plated brass |
| Tesnenie gule | PTFE |
| Tesnenie vretena | HNBR / EPDM / PTFE. 2 O-Rings (HNBR / EPDM) 1 gasket (PTFE) additional PTFE-gasket |



Poznámka

Ďalšie údaje na vyžiadanie.

Výrobok

| Označenie | DN | Závit | A: (mm) | B (mm) | D (mm) |
|----------------|----|---------|------------|-----------|-----------|
| K- 07 30 00 48 | 8 | G 1/4 | 85,0 | 42,0 | 44,0 |
| K- 07 30 00 52 | 10 | G 3/8 | 85,0 | 42,0 | 51,0 |
| K- 07 30 00 56 | 15 | G 1/2 | 85,0 | 46,0 | 60,0 |
| K- 07 30 00 60 | 20 | G 3/4 | 105,0 | 53,0 | 70,0 |
| K- 07 30 00 64 | 25 | G 1 | 105,0 | 57,0 | 79,0 |
| K- 07 30 00 68 | 32 | G 1 1/4 | 130,0 | 70,0 | 91,0 |
| K- 07 30 00 72 | 40 | G 1 1/2 | 130,0 | 76,0 | 104,0 |
| K- 07 30 00 76 | 50 | G 2 | 165,0 | 92,0 | 122,0 |