

K-MANO STAND U

Pressure gauges, CrNi steel, standard type, connection radial on bottom

HANSA FLEX

Vlastnosti

Typ	131.11
Vyhotovenie	Bourdon-tube pressure gauge, CrNi steel type
Použitie	For gaseous, liquid, corrosive and not crystallising media which do not have high viscosity, also in corrosive atmosphere Clean Dry Air applications, machine and plant construction
Akostná trieda	2,5
Teplota média	max. +100 °C
Teplota okolia	-40 °C to +60 °C
Kryt	CrNi steel
Priehľadný kryt stupnice	Polycarbonate



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Standard model manufactured entirely from CrNi steel, economical and reliable.

Výrobok

Označenie	Rozsah merania	Ø (mm)	Pripojka
K- 07 20 03 82	0 - 1.0 bar	40,0	G 1/4
K- 07 20 03 83	0 - 1.6 bar	40,0	G 1/4
K- 07 20 03 84	0 - 2.5 bar	40,0	G 1/4
K- 07 20 03 85	0 - 4.0 bar	40,0	G 1/4
K- 07 20 03 86	0 - 6.0 bar	40,0	G 1/4
K- 07 20 03 87	0 - 10.0 bar	40,0	G 1/4
K- 07 20 03 88	0 - 16.0 bar	40,0	G 1/4
K- 07 20 03 89	0 - 25.0 bar	40,0	G 1/4
K- 07 20 03 90	0 - 40.0 bar	40,0	G 1/4
K- 07 20 03 91	0 - 60.0 bar	40,0	G 1/4
K- 07 20 03 92	0 - 100.0 bar	40,0	G 1/4
K- 07 20 04 83	0 - 1.0 bar	50,0	G 1/4
K- 07 20 04 84	0 - 1.6 bar	50,0	G 1/4
K- 07 20 04 85	0 - 2.5 bar	50,0	G 1/4
K- 07 20 04 86	0 - 4.0 bar	50,0	G 1/4
K- 07 20 04 87	0 - 6.0 bar	50,0	G 1/4
K- 07 20 04 88	0 - 10.0 bar	50,0	G 1/4
K- 07 20 04 89	0 - 16.0 bar	50,0	G 1/4
K- 07 20 04 90	0 - 25.0 bar	50,0	G 1/4
K- 07 20 04 91	0 - 40.0 bar	50,0	G 1/4
K- 07 20 04 92	0 - 60.0 bar	50,0	G 1/4
K- 07 20 04 93	0 - 100.0 bar	50,0	G 1/4