


K-SVKM NW 5 SCHL TUE MS BL1

Quick disconnect couplings DN 5, brass with a bare metal surface, with hose stem

HANSA FLEX

Vlastnosti

Prevádzkový tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
Prietok vzduch	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Teplota média	-20 °C to +100 °C
kryt, puzdro, teleso ventila	Brass
pružina, rozperný krúžok, gule	Stainless steel
Tesniaci materiál	NBR



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. Ideal for: Pneumatic tools, pneumatic applications, medical equipment, instrumentation and control, laboratory, chemical applications, analysis, metering techniques.

Výrobok

Označenie	Prípojka	Dĺžka (mm)
K- 07 35 06 40	Stem, I.D. 4	47,0
K- 07 35 06 52	Stem, I.D. 5	46,0
K- 07 35 06 41	Stem, I.D. 6	46,0
K- 07 35 06 53	Stem, I.D. 8	46,0
K- 07 35 06 42	Stem, I.D. 9	46,0