

K-SVKM NW 7,8 IG H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, female

HANSA FLEX

Vlastnosti

Prevádzkový tlak	0 - 35 bar
Prietok vzduch	2.100 l/min (at $\Delta p = 0.5$ bar)
Teplota média	-20 °C to +40 °C
závitový kus	Nickel-plated brass
teleso ventila	Steel, QPQ treated
uvoľňovacie puzdro	Extremely robust, ergonomic plastic
ventil, sedlo	Brass
Médiá	Only for clean compressed air
Tesnenia	NBR
pružina, rozperný krúžok, gule	stain less steel



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

Výrobok

Označenie	Prípojka	Dĺžka (mm)	SW (mm)
K- 07 35 08 50	G 1/4 female	59,0	19
K- 07 35 08 51	G 3/8 female	59,0	19
K- 07 35 08 52	G 1/2 female	62,0	24

Prídavné elementy

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass