


# K-SVKM NW 7,2 ABSP TUE MS

Quick disconnect couplings DN 7.2, both sides sealing, brass, with hose stem

**HANSA FLEX**

## Vlastnosti

Prevádzkový tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
Prietok vzduch	700 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Teplota média	-20 °C to +100 °C
kryt, puzdro, teleso ventila	Brass
pružina, rozperný krúžok, gule	Stainless steel
Tesniaci materiál	NBR



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Couplings, stems and plugs are fitted with a valve. Connection: Both valves open and the medium is allowed to pass. Disconnection: Both valves close and the medium is prevented from escaping.

## Výrobok

Označenie	Prípojka	Dĺžka (mm)	SW (mm)
K- 07 35 07 56	Stem, I.D. 6	58,0	21
K- 07 35 12 72	Stem, I.D. 8	58,0	21
K- 07 35 07 57	Stem, I.D. 9	58,0	21
K- 07 35 12 74	Stem, I.D. 10	58,0	21
K- 07 35 07 58	Stem, I.D. 13	58,0	21