


# K-SVKM NW 7,2 ABSP TUE MS

Quick disconnect couplings DN 7.2, both sides sealing, brass, with hose stem

**HANSA FLEX**

## Vlastnosti

|                                |   |
|--------------------------------|---|
| Prevádzkový tlak               | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Prietok vzduch                 | 700 l/min (at 6 bar and $\Delta p = 0.5$ bar)               |
| Teplota média                  | -20 °C to +100 °C   |
| kryt, puzdro, teleso ventilu   | Brass   |
| pružina, rozperný krúžok, gule | Stainless steel   |
| Tesniaci materiál              | NBR   |



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Couplings, stems and plugs are fitted with a valve. Connection: Both valves open and the medium is allowed to pass. Disconnection: Both valves close and the medium is prevented from escaping.

## Výrobok

| Označenie      | Prípojka      | Dĺžka (mm) | SW (mm) |
|----------------|---------------|------------|---------|
| K- 07 35 07 56 | Stem, I.D. 6  | 58,0       | 21      |
| K- 07 35 12 72 | Stem, I.D. 8  | 58,0       | 21      |
| K- 07 35 07 57 | Stem, I.D. 9  | 58,0       | 21      |
| K- 07 35 12 74 | Stem, I.D. 10 | 58,0       | 21      |
| K- 07 35 07 58 | Stem, I.D. 13 | 58,0       | 21      |