


K-SVKM NW 7,2 IG MS-NI CL

Quick-lock couplings DN 7.2, nickel-plated brass, female

HANSA FLEX

Vlastnosti

| | |
|----------------------------------|---|
| Prevádzkový tlak | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Teplota média | -20 °C to +100 °C |
| kryt, puzdro, teleso ventila | Nickel-plated brass |
| pružina, rozperný krúžok, kolkky | Stainless steel |
| Tesniaci materiál | NBR |



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Universal, one-hand quick disconnect couplings, one side sealing, at an unbeatably low price. Compatible with CEJN 320, Rectus 25/26 and JWL 520/530. The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

Výrobok

| Označenie | Prípojka | Dĺžka (mm) | SW (mm) |
|----------------|--------------|------------|---------|
| K- 07 35 07 71 | G 1/4 female | 40,5 | 21 |
| K- 07 35 07 72 | G 3/8 female | 40,5 | 21 |
| K- 07 35 07 73 | G 1/2 female | 42,5 | 24 |