

# K-WV 5/2 BEIDS ELEKTRO

5/2-way spool valves, double solenoid

**HANSA FLEX**

## Vlastnosti

<b>Funkcia</b>	5/2-way
<b>Prevádzkový tlak</b>	2.5 - 10 bar; Max. vacuum 10 bar (external pilot air)
<b>min. pracovný tlak</b>	2,5 bar
<b>Rozsah teplôt</b>	-10 °C to +60 °C
<b>Prietok 6bar a 10bar</b>	1500 NI/min (G 1/4), 4600 NI/min (G 1/2)
<b>Elektrické pripojenie</b>	Coupler plug PG 9 - form B
<b>Krytie</b>	IP 65 (DIN 46244)
<b>Kryt</b>	Anodised aluminium, blue
<b>piestový posúvač</b>	Stainless steel
<b>Tesniaci materiál</b>	NBR



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

This valve design, featuring the Tapered Tee Seal®, offers the ability to run without lubrication and supports almost any compressed air quality. The valves are largely resistant to dirt and can thus also be used under extreme conditions without any problems. Leakage is now a thing of the past and the spool no longer sticks, even after long idle periods.

## Výrobok

Označenie	Prípojka	Napätie	DN	Schéma zapojenia číslo	Riadenie
<b>K- 07 15 02 25</b>	G 1/4	24 V DC	8	36	
<b>K- 07 15 02 26</b>	G 1/2"	24 V DC	15	36	
<b>K- 07 15 02 27</b>	G 1/4	230 V AC, 50 Hz	8	36	
<b>K- 07 15 02 28</b>	G 1/2"	230 V AC, 50 Hz	15	36	