

K-LKM S NW7,8 SCHL TUE

Safety couplings DN 7.8, with hose stem

HANSA FLEX

Vlastnosti

Prevádzkový tlak	max. 20 bar
Prietok vzduch	1.400 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Teplota média	-20 °C to +100 °C
Prípojenie telesa ventilátora	Nickel-plated brass
pružina, gule	Stainless-steel
posuvné puzdro	Anodised aluminium
uvoľňovacie puzdro	Hardened and nickel-plated steel
Tesniaci materiál	NBR



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Safety air relief couplings for gaseous media. Combination of a sliding valve and a quick disconnect coupling! Connection is pressureless. Only a low spring force has to be overcome. Pressure only builds up when the blue sleeve is pushed forward. It is impossible to disconnect the hose either intentionally or inadvertently in this position. When the sliding sleeve is moved back into its home position, the air is relieved from the hose and the coupling can be disconnected.

Výrobok

Označenie	Prípojka	Dĺžka (mm)
K- 07 35 08 88	Stem, I.D. 6	86,0
K- 07 35 12 96	Stem, I.D. 8	86,0
K- 07 35 08 89	Stem, I.D. 9	86,0
K- 07 35 12 97	Stem, I.D. 10	86,0
K- 07 35 08 90	Stem, I.D. 13	86,0

Prídavné elementy

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 5 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass