

# K-PRAEZIONS STEUERREGLER

Precision pilot regulators (feedback)

**HANSA FLEX**

## Vlastnosti

|                            |                       |
|----------------------------|-----------------------|
| Vstupný tlak               | Max. 16 bar           |
| Teplota média              | max. 80 °C            |
| Teplota okolia             | Max. 80 °C            |
| Prípojka pre manometer     | For feedback pressure |
| Tesniaci materiál          | FKM                   |
| Kryt                       | Die-cast zinc         |
| Membrána                   | FKM                   |
| Spotreba vlastného vzduchu | 3 to 6 l/min          |



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Diaphragm pressure regulator for feedback systems, specially designed for use in a pneumatically controlled closed control loop in combination with a pressure regulator with pneumatic remote control, e.g. our Art. Nos. K-07250505 to K-07250510.

## Výrobok

| Označenie      | Závit | Rozsah regulácie | A:<br>(mm) | B        | C<br>(mm) | D:<br>(mm) |
|----------------|-------|------------------|------------|----------|-----------|------------|
| K- 07 25 05 11 | G 1/4 | 0.2 - 7 bar      | 82,0       | 142,8 mm | 19,4      | 123,4      |

## Príslušenstvo

K-HALTERBAUSATZ STANDARD Holder