

K-PRAEZI DRUCKREGL OHNE EIGENLUF

Precision pressure regulators without air consumption

HANSA FLEX

Vlastnosti

| | |
|------------------------|--|
| Vstupný tlak | Max. 16 bar |
| Teplota média | max. 80 °C |
| Teplota okolia | Max. 80 °C |
| Médiá | Fine-filtered (5 µm), unlubricated compressed air, neutral gases |
| Prípojka pre manometer | G 1/4 |
| Tesniaci materiál | NBR |
| Kryt | Die-cast zinc |
| guľa ventila, membrána | FPM |



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Diaphragm pressure regulators with self-relieving design for applications requiring an accurate working pressure.

Výrobok

| Označenie | Závit | Rozsah regulácie | Prietok (L/min) | A: (mm) | B | C (mm) | D: (mm) |
|----------------|-------|------------------|-----------------|---------|----------|--------|---------|
| K- 07 25 09 39 | G 1/4 | 0 - 1 bar | 600 | 82,0 | 148,0 mm | 19,5 | 128,5 |
| K- 07 25 09 40 | G 1/4 | 0.1 - 3 bar | 760 | 82,0 | 148,0 mm | 19,5 | 128,5 |
| K- 07 25 09 41 | G 1/4 | 0.2 - 6 bar | 550 | 82,0 | 148,0 mm | 19,5 | 128,5 |
| K- 07 25 09 42 | G 1/4 | 0.5 - 10 bar | 400 | 82,0 | 148,0 mm | 19,5 | 128,5 |

Príslušenstvo

K-HALTERBAUSATZ STANDARD Holder