


# K-SVKM NW 7,2 SCHL-TUE MS BL CL

Quick disconnect couplings DN 7.2, brass with a bare metal surface, with hose stem

**HANSA FLEX**

## Vlastnosti

|                                  |   |
|----------------------------------|---|
| Prevádzkový tlak                 | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Teplota média                    | -20 °C to +100 °C   |
| kryt, puzdro, teleso ventila     | Brass   |
| Tesniaci materiál                | NBR   |
| pružina, rozperný krúžok, kolkky | Stainless steel   |



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Universal, one-hand quick disconnect couplings, one side sealing, at an unbeatably low price. Compatible with CEJN 320, Rectus 25/26 and JWL 520/530. The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

## Výrobok

| Označenie      | Prípojka      | Dĺžka (mm) |
|----------------|---------------|------------|
| K- 07 35 07 45 | Stem, I.D. 6  | 54,0       |
| K- 07 35 07 46 | Stem, I.D. 9  | 54,0       |
| K- 07 35 07 47 | Stem, I.D. 13 | 53,5       |
| K- 07 35 07 48 | Stem, I.D. 8  | 54,0       |
| K- 07 35 07 49 | Stem, I.D. 10 | 54,0       |