

# K-SVKM NW 5 SCHL UEB MS BL

Quick disconnect couplings DN 5, brass with a bare metal surface, with swivel nut and kink protector spring

**HANSA FLEX**

## Vlastnosti

|                                |   |
|--------------------------------|---|
| Prevádzkový tlak               | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Prietok vzduch                 | 560 l/min (at 6 bar and $\Delta p = 0.5$ bar)               |
| Teplota média                  | -20 °C to +100 °C   |
| kryt, puzdro, teleso ventila   | Brass   |
| pružina, rozperný krúžok, gule | Stainless steel   |
| Tesniaci materiál              | NBR   |



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. Ideal for: Pneumatic tools, pneumatic applications, medical equipment, instrumentation and control, laboratory, chemical applications, analysis, metering techniques.

## Výrobok

| Označenie      | Prípojka              | Vyhotovenie     | Dĺžka (mm) | SW (mm) |
|----------------|-----------------------|-----------------|------------|---------|
| K- 07 35 06 48 | Hose connection 6 x 4 | Rigid           | 120,0      | 14      |
| K- 07 35 06 49 | Hose connection 8 x 6 | Rigid           | 132,0      | 14      |
| K- 07 35 06 50 | Hose connection 6 x 4 | Swivelling 360° | 134,0      | 14      |
| K- 07 35 06 51 | Hose connection 8 x 6 | Swivelling 360° | 145,0      | 14      |