


K-SVKM NW 7,2 SCHL-ANSCHL MS

Quick disconnect couplings DN 7.2, nickel-plated brass, with hose connector, with swivel nut

HANSA FLEX

Vlastnosti

Prevádzkový tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
Prietok vzduch	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Teplota média	-20 °C to +100 °C
kryt, puzdro	Nickel-plated brass
Ventil	Brass with a bare metal surface
pružina, rozpěrný krúžok	Stainless steel 1.4310
blokovacie koflíky	Stainless steel 1.4034
Tesniaci materiál	NBR



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

Výrobok

Označenie	Prípojka	Dĺžka (mm)	SW (mm)
K- 07 35 12 67	Hose connection 6 x 4	58,0	21
K- 07 35 07 24	Hose connection 8 x 6	45,0	21
K- 07 35 07 25	Hose connection 10 x 8	49,0	21
K- 07 35 07 26	Hose connection 12 x 9	49,0	21

Prídavné elementy

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass