


# K-VENTILSCHEIBE HDM 8

Valve discs for HDM valve terminal with 8 mm port

**HANSA FLEX**

## Vlastnosti

Médiá	Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
Pracovný tlak	Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)
Riadiaci tlak	3 - 7 bar
Rozsah teplôt	-10 °C to +60 °C
Prietok	200 Nl/min (Ø 4), 500 Nl/min (Ø 6), 800 Nl/min (Ø 8)
Počet ovládaní	Max. 16 (e.g. 16 spring return valves)
Aretácia	Latching (bistable), Monostable (non-latching) version also available on request
Príkon	0.6 W per pilot
Krytie	IP 65



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

These compact valve terminals, with a maximum flow rate of 800 Nl/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

## Dodatočné informácie

Important: The scope of supply does not include a connector. Please order separately.

## Výrobok

Označenie	funkcia
K-07 15 20 69	2 x 3/2-way, NC, monostable or 5/3-way, mid-position exhausted
K-07 15 20 72	2 x 3/2-way, NO, monostable or 5/3-way, mid-position pressurised
K-07 15 20 63	3/2-way, NC, monostable and 3/2-way, NO, monostable
K-07 15 20 71	5/2-way, monostable
K-07 15 20 68	5/2-way, monostable (uses only one pin, two signals assigned)
K-07 15 20 70	5/2-way, bistable (pulse valve)
K-07 15 20 65	5/3-way, mid-position closed