

K-ELEKTRISCHE ANSCHLUESSE

Electrical connection (multi-pole, 25-pin, IP 65)

HANSA FLEX

Vlastnosti

| | |
|-----------------------|---|
| Médiá | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| Pracovný tlak | Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard) |
| Riadiaci tlak | 3 - 7 bar |
| Rozsah teplôt | -10 °C to +60 °C |
| Prietok | 200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8) |
| Počet ovládaní | Max. 16 (e.g. 16 spring return valves) |
| Aretácia | Latching (bistable), Monostable (non-latching) version also available on request |
| Príkonn | 0.6 W per pilot |
| Krytie | IP 65 |



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Dodatočné informácie

Important: The scope of supply does not include a connector. Please order separately.

Výrobok

| Označenie | Definícia |
|----------------|---|
| K- 07 15 22 45 | IP 67 connector, 25-pin, with 1 m cable |
| K- 07 15 22 46 | IP 67 connector, 25-pin, with 2.5 m cable |
| K- 07 15 22 47 | IP 67 connector, 25-pin, with 5 m cable |