


K-NEBELOELER PC-BEHÄLTER S VARIOBL

Oil-mist lubricators with polycarbonate bowl and bowl guard

HANSA FLEX

Vlastnosti

| | |
|--------------------------------|--|
| Vstupný tlak | Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl) |
| Teplota média | max. 50 °C |
| Teplota okolia | Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl) |
| Tesniaci materiál | NBR |
| Kryt | Die-cast zinc |
| Vložka kvapkadla | PA |
| Druh oleja | CL 32 acc. to DIN 51517 - ISO VG 32 |
| Meranie prietochového množstva | At P1 = 6 bar and pressure drop $\Delta p = 1$ bar |



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Proportional lubricators, oil can be filled under pressure. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

Pokyny pre objednanie

Oil-mist lubricators are also available with bowl guard or metal bowl.

Výrobok

| Označenie | Závit | Prietok (L/min) | A: (mm) | B | C (mm) |
|----------------|-------|-----------------|---------|----------|--------|
| K- 07 25 22 87 | G 1 | 7500 | 124,0 | 224,0 mm | 57,0 |
| K- 07 25 22 88 | G 3/4 | 7500 | 70,0 | 224,0 mm | 57,0 |
| K- 07 25 22 89 | G 1/2 | 4600 | 70,0 | 224,0 mm | 57,0 |
| K- 07 25 22 90 | G 3/8 | 4400 | 48,0 | 171,0 mm | 52,0 |
| K- 07 25 22 91 | G 1/4 | 3400 | 48,0 | 171,0 mm | 52,0 |