


# K-MV G (NC) D 24 V DC H 1

Normally closed, (NC), directly operated, 24 V DC, for high pressures

**HANSA FLEX**

## Vlastnosti

|                              |   |
|------------------------------|---|
| <b>Elektrické pripojenie</b> | device socket type A in acc. with ISO 4400 for all valves with threads G 3/8 & G 1/2, except valves type 3 & 4. Device socket |
| <b>Krytie</b>                | IP 65   |
| <b>Teplota média</b>         | max. 80 °C when using water or oils; max. 90 °C when using with air   |
| <b>Popis závitú</b>          | G thread acc. DIN EN ISO 228-1  |
| <b>kryt, sedlo ventíla</b>   | Brass   |
| <b>vnútorné diely</b>        | Stainless steel   |
| <b>tesnenie</b>              | FPM   |



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Standard series in two different versions: Directly operated, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

## Výrobok

| Označenie      | Závit | max. prevádzkový tlak<br>(bar) | MS  | A:<br>(mm) | B<br>(mm) | C<br>(mm) | vyhotovenie |
|----------------|-------|--------------------------------|-----|------------|-----------|-----------|-------------|
| K- 07 30 01 68 | G 1/8 | 30                             | 1,5 | 70,0       | 40,0      | 70,7      | 1           |
| K- 07 30 01 69 | G 1/4 | 30                             | 1,5 | 70,0       | 40,0      | 70,7      | 1           |
| K- 07 30 01 70 | G 3/8 | 30                             | 3,0 | 85,0       | 52,0      | 87,0      | 1           |
| K- 07 30 01 71 | G 1/2 | 30                             | 3,0 | 85,0       | 52,0      | 87,0      | 1           |