


# K-T-STECK VB RED

Union tees, unequal

**HANSA FLEX**

## Vlastnosti

Pracovný tlak	Max. 15 bar, coarse vacuum
Oblasť použitia	Air, vacuum
odporované hadice	PU or PA (nylon)
Médiá	Compressed air and all gases or liquids that are compatible with the materials
Rozsah teplôt	-20 °C to +80 °C
Materiál	Plastic, Nickel plated brass
Prítlačný krúžok	Plastic
Druh pripojenia	



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Výrobok

Označenie	pre vonkajší Ø hadice	L1 (mm)
K- 07 40 03 62	2 x 4 mm / 1 x 6 mm	19,0
K- 07 40 03 63	2 x 6 mm / 1 x 4 mm	19,0
K- 07 40 03 64	2 x 6 mm / 1 x 8 mm	22,0
K- 07 40 41 42	2 x 8 mm / 1 x 4 mm	22,0
K- 07 40 03 65	2 x 8 mm / 1 x 6 mm	22,5
K- 07 40 03 66	2 x 8 mm / 1 x 10 mm	27,5
K- 07 40 41 43	2 x 10 mm / 1 x 6 mm	27,1
K- 07 40 03 67	2 x 10 mm / 1 x 8 mm	27,9
K- 07 40 03 68	2 x 10 mm / 1 x 12 mm	28,9
K- 07 40 41 44	2 x 12 mm / 1 x 8 mm	28,5
K- 07 40 03 69	2 x 12 mm / 1 x 10 mm	29,3
K- 07 40 41 45	2 x 16 mm / 1 x 12 mm	31,8