

K-LKM S NW7,4 DREH IG VA

Safety couplings DN 7.4, stainless steel 1.4404, female, swivel type

HANSA FLEX

Vlastnosti

Prevádzkový tlak	max. 10 bar
Prietok vzduch	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Teplota média	-20 °C to +150 °C
Kryt	Stainless steel 1.4404
závit	Stainless steel 1.4404
vnútorné diely	Stainless steel 1.4404
gombík, ventil	Stainless steel 1.4404
Tesniaci materiál	FKM



Poznámka

Not suitable for hitting / pulsating tools.

Ďalšie údaje na vyžiadanie.

Popis

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Dodatočné informácie

Not suitable for hitting / pulsating tools.

Výrobok

Označenie	Prípojka	Dĺžka (mm)	SW (mm)
K- 07 35 12 79	G 1/4 female	71,5	21
K- 07 35 12 80	G 3/8 female	75,5	21
K- 07 35 12 81	G 1/2 female	77,5	24