

K-DMUF FESTSTOFFHALTIGE MED

Pressure transmitter for viscous and solids-containing media,
nonlinearity 0.2%

HANSA FLEX

Vlastnosti

Typ	S-11
Napätie	DC 10 (14) ... 30 V
Elektrické pripojenie	With right-angle connector acc. to DIN EN 175301-803 A
Krytie	IP 65 acc. to EN 60529
Výstupný signál	4 to 20 mA, 2-wire
Nelinearita	0.2% of span
Teplota média	-30 °C to +100 °C; (Range: 400 and 600 bar: -30 °C to +70 °C)
Teplota okolia	-20 °C to +80 °C
Časť dotýkajúca sa meranej látky	CrNi steel 1.4571
Kryt	CrNi steel 1.4571



Popis

Pressure transmitter in CrNi steel with flush diaphragm for measuring viscous, pasty, adhesive, crystallising, particle-laden or contaminated media, which would clog the pressure channel of conventional process connections. Applications: Electronic pressure measurement in the food and beverages sector, hydraulic power units or industrial applications in general.

Dodatočné informácie

Further measuring ranges on request

There are also pressure converters with cooling fins available optionally on request for high media temperatures (up to +150 °C).

Výrobok

Označenie	Rozsah merania	Závit
K- 07 20 12 38	0 - 0.25 bar	G 1
K- 07 20 12 39	0 - 0.4 bar	G 1
K- 07 20 12 40	0 - 1.0 bar	G 1
K- 07 20 12 41	0 - 10.0 bar	G 1/2
K- 07 20 12 42	0 - 100.0 bar	G 1/2
K- 07 20 12 43	0 - 16.0 bar	G 1/2
K- 07 20 12 44	0 - 160.0 bar	G 1/2
K- 07 20 12 45	0 - 25.0 bar	G 1/2
K- 07 20 12 46	0 - 250.0 bar	G 1/2
K- 07 20 12 47	0 - 4.0 bar	G 1/2
K- 07 20 12 48	0 - 40.0 bar	G 1/2
K- 07 20 12 49	0 - 400.0 bar	G 1/2
K- 07 20 12 50	0 - 6.0 bar	G 1/2
K- 07 20 12 51	0 - 60.0 bar	G 1/2
K- 07 20 12 52	0 - 600.0 bar	G 1/2

Náhradné diely

K-ZUBEH DRUCKMESSUMFOR Accessoires for pressure transmitters for viscous and solids-containing media, nonlinearity 0.2%