


K-WERKST-SCHLAUCH SOFT

Workshop hose soft

HANSA FLEX

Vlastnosti

Vnútorá vrstva	Soft-PVC, black
Vnútorá vložka	Polyesterový výplet
Vonkajšia vrstva	Soft-PVC, blue
Teplota	-20 °C to +60 °C
Dĺžka kladky	50 m



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

Výrobok

Označenie	vnútorný Ø hadice (mm)	vonkajší Ø hadice (mm)	Max. working pressure resistance at 23°C (bar)	Polomer ohybu min. (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88