


K-DLV MULTI-LINK SCHNELLVER

Compressed air distributor, type »Multi-Link« quick disconnect safety couplings DN 7.6

HANSA FLEX

Vlastnosti

| | |
|-------------------|-------------------------------------|
| Prevádzkový tlak | Max. 16 bar |
| Rozsah teplôt | -20 °C to +80 °C |
| Materiál | Galvanised steel / brass |
| Prípojka | G 1/2 female |
| Médiá | Compressed air, non-corrosive gases |
| Tesniaci materiál | NBR |



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Modular distributor system for flexible workplace design, can be rotated 180°. Equipped for 1 to 5 bleed units:
- DN 7.6 quick disconnect safety couplings.

Výrobok

| Označenie | Prípojka | Odberové jednotky |
|----------------|-------------------------|-------------------|
| K- 07 35 13 70 | Safety couplings DN 7.6 | 1 |
| K- 07 35 13 73 | Safety couplings DN 7.6 | 2 |
| K- 07 35 13 76 | Safety couplings DN 7.6 | 3 |
| K- 07 35 13 79 | Safety couplings DN 7.6 | 4 |
| K- 07 35 13 82 | Safety couplings DN 7.6 | 5 |