

# K-LECKAGESUCHGERAET

Leakage finder

**HANSA FLEX**

## Vlastnosti

Pracovná frekvencia	40 kHz $\pm$ 2 kHz
Prípojka	4-pin connection for headphones and charger, 3.5 mm stereo jack for connecting sensor and cable
Laser	Wave length: 655 to 660 nm, Output power: 0.4 to 0.5 mW
Zásobovanie energiou	Internal NiMH rechargeable battery
Trvanie prevádzky	Approx. 6 hours without laser / 4 hours with laser
Čas nabíjania	Approx. 1.5 hours
Teplota použitia	0 °C to +40 °C
Teplota skladovania	-10 °C to +50 °C



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Function: The annual energy cost of leaks in pneumatic and gas systems are high and avoidable. When these gases flow unused out of leaks, they create noises inaudible to the human ear. With the LS 100, even the smallest leaks can be heard from several metres distance. It transforms inaudible signals to a frequency that can be detected visually on the display and acoustically with the supplied sound-proof headphones. Use: leakage inspections of pneumatic, gas, steam and vacuum systems. <br>The advantages of the LS 100: Simple and quick measurement, even from distances of several metres  
Measurements can be taken on running systems, without affecting their operation  
The device is quickly amortised by the high cost savings

## Výrobok

Označenie	Popis
K- 07 25 19 53	Leak detection device, including accessories in a practical carrying case

## Príslušenstvo

K-ALU-TELESKOPSTANGE	Aluminium-telescopic pole
----------------------	---------------------------