K-SPIR SCHL KUPPL SET STAND MS

Spiral hose and coupling kit with standard coupling and push-in plug, bare brass

Vlastnosti

Druh pripojenia	connection nipples and coupling NW 7,2
Prevádzková teplota	-40 °C to +74 °C



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Výrobok

Označenie	vnútorný Ø hadice (mm)	vonkajší Ø hadice (mm)	Ø vonkajšie vinutie (mm)	Max. working pressure resistance at 23°C (bar)	max. pracovná dĺžka (m)
K- 07 10 12 72	5,0	8,0	40	10	3,0
K- 07 10 12 74	5,0	8,0	40	10	6,0
K- 07 10 12 76	5,0	8,0	40	10	7,5
K- 07 10 12 81	6,3	9,5	60	10	3,0
K- 07 10 12 83	6,3	9,5	60	10	6,0
K- 07 10 12 85	6,3	9,5	60	10	7,5
K- 07 10 12 79	6,3	9,5	60	10	10,0
K- 07 10 12 90	8,0	12,0	80	9	3,0
K- 07 10 12 92	8,0	12,0	80	9	6,0
K- 07 10 12 94	8,0	12,0	80	9	7,5
K- 07 10 12 88	8,0	12,0	80	9	10,0

Príslušenstvo

K-DREHBARE VERSCHRAUBUNG	Swivel adapters