

# K-SPIR SCHL KUPPL SET LKM NW 7,4

Spiral hose and coupling kit with pushbutton-type safety coupling (DN 7.4) and push-in plug, galvanised steel

**HANSA FLEX**

## Vlastnosti

|                     |  |
|---------------------|--|
| Druh pripojenia     | with pushbutton safety coupling NW 7,4 steel nipple galvanised |
| Prevádzková teplota | -40 °C to +74 °C   |



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Nie je vhodné pre udierajúce alebo pulzujúce nástroje!

## Výrobok

| Označenie      | vnútorný Ø hadice (mm) | vonkajší Ø hadice (mm) | Ø vonkajšie vinutie (mm) | Max. working pressure resistance at 23°C (bar) | max. pracovná dĺžka (m) |
|----------------|------------------------|------------------------|--------------------------|--|-------------------------|
| K- 07 10 12 71 | 5,0                    | 8,0                    | 40                       | 10   | 3,0                     |
| K- 07 10 12 73 | 5,0                    | 8,0                    | 40                       | 10   | 6,0                     |
| K- 07 10 12 75 | 5,0                    | 8,0                    | 40                       | 10   | 7,5                     |
| K- 07 10 12 80 | 6,3                    | 9,5                    | 60                       | 10   | 3,0                     |
| K- 07 10 12 82 | 6,3                    | 9,5                    | 60                       | 10   | 6,0                     |
| K- 07 10 12 84 | 6,3                    | 9,5                    | 60                       | 10   | 7,5                     |
| K- 07 10 12 78 | 6,3                    | 9,5                    | 60                       | 10   | 10,0                    |
| K- 07 10 12 89 | 8,0                    | 12,0                   | 80                       | 9  | 3,0                     |
| K- 07 10 12 91 | 8,0                    | 12,0                   | 80                       | 9  | 6,0                     |
| K- 07 10 12 93 | 8,0                    | 12,0                   | 80                       | 9  | 7,5                     |
| K- 07 10 12 87 | 8,0                    | 12,0                   | 80                       | 9  | 10,0                    |

## Príslušenstvo

K-DREHBARE VERSCHRAUBUNG Swivel adapters