

# TR A

Vsuvka k narážaniu, DKM

**HANSA FLEX**

## Vlastnosti

|                   |                           |
|-------------------|---------------------------|
| Prípojka 1        | metrický závit pre matice |
| Tvar tesnenia 1   | Tesniaca hlava 60°        |
| Norma             | DIN 3863                  |
| Materiál          | Oceľ                      |
| Povrchová ochrana | galvanický povlak         |



## Výrobok

| Označenie  | DN | Rozmer | Clo   | G1         | L1<br>(mm) | S1 |
|------------|----|--------|-------|------------|------------|----|
| TR 04 A    | 5  | 3      | 3/16" | M 12 x 1,5 | 28         | 14 |
| TR 06 A    | 6  | 4      | 1/4"  | M 14 x 1,5 | 28         | 17 |
| TR 06 A 08 | 6  | 4      | 1/4"  | M 16 x 1,5 | 28         | 19 |
| TR 08 A    | 8  | 5      | 5/16" | M 16 x 1,5 | 34         | 19 |
| TR 10 A 08 | 10 | 6      | 3/8"  | M 16 x 1,5 | 34         | 19 |
| TR 10 A    | 10 | 6      | 3/8"  | M 18 x 1,5 | 34         | 22 |
| TR 13 A    | 12 | 8      | 1/2"  | M 22 x 1,5 | 45         | 27 |