

K-W STECK VB 2-FACH WAND 20-63 INFI

2-fold angle connector Ø 20 mm - Ø 63 mm with wall mounting
(adjustable)

HANSA FLEX

Vlastnosti

Médiá	Compressed air, vacuum, inert gases
Prevádzkový tlak	-0,99 bar - 15 bar
Rozsah teplôt	-20 °C to +80 °C
tesnenie	NBR
Kryt	Nickel-plated brass
zvierací krúžok	Stainless steel 1.4301
matica	Nickel-plated brass
O-krúžok	NBR
poistný krúžok	Technopolymer



Výrobok

Označenie	Vonkajší Ø rúrky	Prípojka	B	C	E	I	L1	L2	L max	L min	M	N	O	P	SW1	SW2
			(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
K- 07 40 54 14	20 mm	G 1/2"	31,5	20,0	34,5	28,5	27,0	51,5	54	22	74	61	30,5	5	26	30
K- 07 40 54 15	25 mm	G 1/2"	38,5	21,0	42,5	28,5	27,0	59,0	54	22	74	61	30,5	5	26	35